



SAFETY DATA SHEET CERAMIC EXPRESS WAX WITH LASTING PROTECTION

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CERAMIC EXPRESS WAX WITH LASTING PROTECTION

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Iain Semple Chemicals Ltd
7 McKenzie St,
Paisley,
Renfrewshire,
PA3 1LX
0141 8487557

1.4. Emergency telephone number

Emergency telephone +44 (0) 141 8487557 (Mon - Fri 9:00am - 5:00pm GMT)

National emergency telephone number +44 (0)870 600 6266 [UK National Poisons Control Information Service (NPIS) Center]

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318
Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 Keep container tightly closed.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p>
Contains	aminomodified polydimethylsiloxane
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

propan-2-ol	10-30%
CAS number: 67-63-0	EC number: 200-661-7
	REACH registration number: 01-2119457558-25-XXXX
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
2-butoxyethanol	5-10%
CAS number: 111-76-2	EC number: 203-905-0
	REACH registration number: 01-2119475108-36-XXXX
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Siloxanes and Silicones, 3- [(2-aminoethyl)amino]propyl Me, di-Me, hydroxyterminated	1-5%
CAS number: 75718-16-0	
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Corr. 1A - H314	C; R35

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

3-butoxypropan-2-ol		1-5%
CAS number: 5131-66-8	EC number: 225-878-4	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	Classification (67/548/EEC or 1999/45/EC) Xi; R36/38	
methanol		<1%
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01-2119433307-44-XXXX
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC or 1999/45/EC) F; R11. T; R39/23/24/25, R23/24/25	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	If in doubt, get medical attention promptly.
Inhalation	Get medical attention if any discomfort continues.
Ingestion	Give plenty of water to drink. Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Rinse with water.
Eye contact	Get medical attention if any discomfort continues. Remove affected person from source of contamination. Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Inhalation	May cause discomfort. May be harmful if inhaled.
Ingestion	A single exposure may cause the following adverse effects: Nausea, vomiting. May be harmful if swallowed.
Skin contact	May be harmful in contact with skin. May cause discomfort. Prolonged and frequent contact may cause redness and irritation.
Eye contact	May be slightly irritating to skin and eyes. Prolonged or repeated exposure may cause severe irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
Specific treatments	Not applicable.

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media None known.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable.

Hazardous combustion products None known.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours.

Special protective equipment for firefighters Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact.

6.2. Environmental precautions

Environmental precautions No negative effects on the aquatic environment are known. Not regarded as dangerous for the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand, earth or other suitable non-combustible material. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin, eyes and clothing. Avoid contact with eyes and prolonged skin contact.

Advice on general occupational hygiene Clean equipment and the work area every day. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container. Keep container tightly closed in a cool place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

propan-2-ol

EH40 WEL, Time Weighted Average (TWA): 400ppm, 999mg/m³

EH40 WEL, Short Term Exposure Limit (STEL): 500ppm, 1250 mg/m³

ELV (IE), Short Term Exposure Limit (STEL): 400 ppm

ELV (IE), Time Weighted Average (TWA): 200 ppm

2-butoxyethanol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

Sk

methanol

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

Sk

Sk = Can be absorbed through the skin.

propan-2-ol (CAS: 67-63-0)

DNEL	Workers - Dermal; Long term systemic effects: 888 mg/kg/day Workers - Inhalation; Long term systemic effects: 500 mg/m ³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m ³ Consumer - Oral; Long term systemic effects: 26 mg/kg/day
PNEC	- Fresh water; 140.9 mg/l - marine water; 140.9 mg/l - Intermittent release; 140.9 mg/l - STP; 2251 mg/l - Sediment; 552 mg/kg - Soil; 28 mg/kg

2-butoxyethanol (CAS: 111-76-2)

Ingredient comments	WEL = Workplace Exposure Limit
DNEL	Industry - Dermal; Short term systemic effects: 89 mg/kg/day Industry - Inhalation; Short term systemic effects: 1091 mg/m ³ Industry - Inhalation; Short term local effects: 246 mg/m ³ Industry - Dermal; Long term systemic effects: 125 mg/kg/day Industry - Inhalation; Long term systemic effects: 98 mg/m ³ Consumer - Inhalation; Short term systemic effects: 426 mg/m ³ Consumer - Oral; Short term systemic effects: 26.7 mg/kg/day Consumer - Dermal; Short term systemic effects: 89 mg/kg/day Consumer - Dermal; Long term systemic effects: 75 mg/kg/day Consumer - Inhalation; Long term local effects: 147 mg/m ³ Consumer - Inhalation; Long term systemic effects: 59 mg/m ³ Consumer - Oral; Long term systemic effects: 6.3 mg/kg/day

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

PNEC	Fresh water; 8.8 mg/l
	marine water; 0.88 mg/l
	Sediment (Freshwater); 8.14 mg/kg
	Sediment (Marinewater); 3.46 mg/kg
	Soil; 2.8 mg/kg
	STP; 463 mg/l

methanol (CAS: 67-56-1)

DNEL	Industry - Dermal; Long term systemic effects: 40 mg/kg/day
	Industry - Inhalation; Long term systemic effects: 260 mg/m ³
	Industry - Dermal; Short term systemic effects: 40 mg/kg/day
	Industry - Inhalation; Short term systemic effects: 260 mg/m ³
	Consumer - Dermal; Long term systemic effects: 8 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 50 mg/m ³
	Consumer - Dermal; Short term systemic effects: 8 mg/kg/day
	Consumer - Inhalation; Short term systemic effects: 50 mg/m ³
	Consumer - Oral; Short term systemic effects: 8 mg/kg/day

PNEC	Sediment; 570.4 mg/kg
	Soil; 23.5 mg/kg
	STP; 100 mg/l
	Fresh water; 154 mg/l
	marine water; 15.4 mg/l
	Intermittent release; 1540 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Contact lenses should not be worn when working with this chemical. Chemical splash goggles.

Hand protection

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Eye wash facilities and emergency shower must be available when handling this product. Wash promptly with soap and water if skin becomes contaminated. Wash contaminated clothing before reuse.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

Appearance	Opaque liquid.
Colour	White.
Odour	Alcoholic.
pH	pH (concentrated solution): 4.5-5.5
Flash point	~ 40°C
Relative density	0.98 @ 20°C
Solubility(ies)	Soluble in water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight. Avoid freezing.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products May emit toxic fumes under fire conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 14,192.14

Acute toxicity - dermal

ATE dermal (mg/kg) 13,681.59

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 136.82

Inhalation Vapours may irritate throat/respiratory system. May be harmful if inhaled.

Ingestion May cause discomfort if swallowed. May be harmful if swallowed.

Skin contact Prolonged skin contact may cause redness and irritation. May be harmful in contact with skin.

Eye contact May cause irritation. May cause serious eye damage.

Toxicological information on ingredients.

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

propan-2-ol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 13,900.0

Species Rabbit

ATE dermal (mg/kg) 13,900.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 25.0

Species Rat

2-butoxyethanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,300.0

Species Rat

ATE oral (mg/kg) 1,300.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Guinea pig

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 2.39

Species Rat

ATE inhalation (gases ppm) 4,500.0

ATE inhalation (vapours mg/l) 11.0

ATE inhalation (dusts/mists mg/l) 1.5

SECTION 12: Ecological information

Ecotoxicity

The product is not expected to be hazardous to the environment.

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

12.1. Toxicity

Ecological information on ingredients.

propan-2-ol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates LC₅₀, 24 hours: 9714 mg/l, Daphnia magna

Acute toxicity - microorganisms EC₅₀, 72 hours: >100 mg/l, Scenedesmus subspicatus (algae)

2-butoxyethanol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1474 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 1550 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 1840 mg/l,

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 100 mg/l, Daphnia magna

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1987

UN No. (IMDG) 1987

UN No. (ICAO) 1987

UN No. (ADN) 1987

14.2. UN proper shipping name

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

Proper shipping name (ADR/RID) ALCOHOLS, N.O.S. (ISOPROPANOL)

Proper shipping name (IMDG) ALCOHOLS, N.O.S. (ISOPROPANOL)

Proper shipping name (ICAO) ALCOHOLS, N.O.S. (ISOPROPANOL)

Proper shipping name (ADN) ALCOHOLS, N.O.S. (ISOPROPANOL)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

CERAMIC EXPRESS WAX WITH LASTING PROTECTION

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Only trained personnel should use this material.

Issued by HS&E Manager.

Revision date 06/03/2019

Revision 6

Supersedes date 06/03/2019

SDS number 8305

Hazard statements in full H225 Highly flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H370 Causes damage to organs (Eyes, Central nervous system).

Code

Other Information

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.